



KABELOVÁ VÝVODKA MOSAZNÁ IP68 VITON*

íslo výroby: HSK-M HT
 Teplotní rozsah: -25 °C + 230 °C
 Krytí : IP 68 - 5 bar
MATERIÁL:
 T lo vývodky: poniklovaná mosaz
 Vnit ní tvarová vložka: Viton
 O-kroužek : Viton




kat.	závit F	O kabelu (mm)
HSK-MM12HTA	M12 x 1,5	5,0 ÷ 7,0
HSK-MM16HTA	M16 x 1,5	5,0 ÷ 7,0
HSK-MM16HTB	M16 x 1,5	8,0 ÷ 10,0
HSK-MM20HTA	M20 x 1,5	7,0 ÷ 10,0
HSK-MM20HTB	M20 x 1,5	11,0 ÷ 14,0
HSK-MM25HTA	M25 x 1,5	11,0 ÷ 14,0
HSK-MM25HTB	M25 x 1,5	15,0 ÷ 19,0
HSK-MM32HTA	M32 x 1,5	15,0 ÷ 18,0
HSK-MM32HTB	M32 x 1,5	19,0 ÷ 22,0
HSK-MM40HTA	M40 x 1,5	21,0 ÷ 24,0
HSK-MM40HTB	M40 x 1,5	25,0 ÷ 28,0

M




KABELOVÁ VÝVODKA Z NEREZOVÉ OCELI IP68

íslo výroby: HSK-X
 Teplotní rozsah: -40 °C + 120 °C
 Krytí : IP 68 - 5 bar
MATERIÁL:
 T lo vývodky: nerezová ocel AISI 303 (1.4305)
 Vnit ní tvarová vložka: TPE
 O-kroužek : NBR-Oz




kat.	závit F	O kabelu (mm)
HSK-XM12	M12 x 1,5	5,0 ÷ 7,0
HSK-XM16	M16 x 1,5	5,0 ÷ 10,0
HSK-XM20	M20 x 1,5	9,0 ÷ 14,0
HSK-XM25	M25 x 1,5	13,0 ÷ 19,0
HSK-XM32	M32 x 1,5	15,0 ÷ 22,0
HSK-XM40	M40 x 1,5	22,0 ÷ 28,0

M




KABELOVÁ VÝVODKA Z NEREZOVÉ OCELI IP68 VITON*

íslo výroby: HSK-X HT
 Teplotní rozsah: -25 °C + 230 °C
 Krytí : IP 68 - 5 bar
MATERIÁL:
 T lo vývodky: nerezová ocel AISI 303 (1.4305)
 Vnit ní tvarová vložka: Viton
 O-kroužek : Viton



kat.	závit F	O kabelu (mm)
HSK-XM12HTA	M12 x 1,5	5,0 ÷ 7,0
HSK-XM16HTA	M16 x 1,5	5,0 ÷ 7,0
HSK-XM16HTB	M16 x 1,5	8,0 ÷ 10,0
HSK-XM20HTA	M20 x 1,5	7,0 ÷ 10,0
HSK-XM20HTB	M20 x 1,5	11,0 ÷ 14,0
HSK-XM25HTA	M25 x 1,5	11,0 ÷ 14,0
HSK-XM25HTB	M25 x 1,5	15,0 ÷ 19,0
HSK-XM32HTA	M32 x 1,5	15,0 ÷ 18,0
HSK-XM32HTB	M32 x 1,5	19,0 ÷ 22,0
HSK-XM40HTA	M40 x 1,5	21,0 ÷ 24,0
HSK-XM40HTB	M40 x 1,5	25,0 ÷ 28,0

M



* termín dodání na poptání