



HSK - M / HSK - M E

KABELOVÁ VÝVODKA MOSAZNÁ IP68

íslo výrobku: HSK-MM / HSK-MP
 Pracovní teplota: -30 °C + 120 °C
 Krytí systému: IP 68 - 5 bar

CHARAKTERISTICKÉ VLASTNOSTI:

Vyrobeno z poniklované mosazi
 Sv rná vložka: polyamid PA6
 T sn ní: perbunan - NBR

kat.	závit F	O kabelu (mm)
HSK-MM12	M12 x 1,5	3,0 ÷ 6,5
HSK-MM16	M16 x 1,5	4,5 ÷ 10,0
HSK-MM20	M20 x 1,5	6,0 ÷ 12,0
HSK-MM25	M25 x 1,5	11,0 ÷ 17,0
HSK-MM32	M32 x 1,5	15,0 ÷ 21,0
HSK-MM40	M40 x 1,5	19,0 ÷ 28,0
HSK-MM50	M50 x 1,5	27,0 ÷ 38,0
HSK-MM63	M63 x 1,5	34,0 ÷ 44,0

M

kat.	závit F	O kabelu (mm)
HSK-MP7	7	3,0 ÷ 6,5
HSK-MP9	9	4,0 ÷ 8,0
HSK-MP11	11	5,0 ÷ 10,0
HSK-MP13	13,5	6,0 ÷ 12,0
HSK-MP16	16	10,0 ÷ 14,0
HSK-MP21	21	13,0 ÷ 18,0
HSK-MP29	29	18,0 ÷ 25,0
HSK-MP36	36	22,0 ÷ 32,0
HSK-MP42	42	32,0 ÷ 38,0
HSK-MP48	48	37,0 ÷ 44,0

PG

KABELOVÁ VÝVODKA MOSAZNÁ IP68 EMC

íslo výrobku: HSK-MM E / HSK-MP E
 Pracovní teplota: -30 °C + 120 °C
 Krytí systému: IP 68 - 5 bar

CHARAKTERISTICKÉ VLASTNOSTI:

Vyrobeno z poniklované mosazi
 Sv rná vložka: polyamid PA6

kat.	závit F	O kabelu (mm)
HSK-MM12E	M12 x 1,5	3,0 ÷ 6,5
HSK-MM16E	M16 x 1,5	4,5 ÷ 10,0
HSK-MM20E	M20 x 1,5	6,0 ÷ 12,0
HSK-MM25E	M25 x 1,5	11,0 ÷ 17,0
HSK-MM32E	M32 x 1,5	15,0 ÷ 21,0
HSK-MM40E	M40 x 1,5	19,0 ÷ 28,0
HSK-MM50E	M50 x 1,5	27,0 ÷ 38,0
HSK-MM63E	M63 x 1,5	34,0 ÷ 44,0

M

kat.	závit F	O kabelu (mm)
HSK-MP7E	7	3,0 ÷ 6,5
HSK-MP9E	9	4,0 ÷ 8,0
HSK-MP11E	11	5,0 ÷ 10,0
HSK-MP13E	13,5	6,0 ÷ 12,0
HSK-MP16E	16	10,0 ÷ 14,0
HSK-MP21E	21	13,0 ÷ 18,0
HSK-MP29E	29	18,0 ÷ 25,0
HSK-MP36E	36	22,0 ÷ 32,0
HSK-MP42E	42	32,0 ÷ 38,0
HSK-MP48E	48	37,0 ÷ 44,0

PG

